



## DLH1000S Tungsten Soft Light

A dedicated single function halogen soft light, exclusively for use with many styles and sizes of soft boxes.

The lamp, which is placed in the focal center of the soft box produces a perfectly lit surface. In comparison to a soft box attachment mounted to a Fresnel fixture, it provides double the light efficiency with no hot spots. Readily available halogen lamps from 500-1000W may be used in this light fixture.

The DLH1000S can be a stand alone light or a companion to the classic tungsten dedolight and Series 400 focusing halogen heads.

A protective glass tube is easily removable for quick lamp change. Many styles and sizes of soft boxes may be used with the integrated speed ring.

Adapts in seconds and without tools to an amazing variety of soft boxes by the function of the innovative variable size speed ring. The diameter is changed by extending the rod receptacles for the soft box in four steps:

130 mm (5.118"), 150 mm (5.9"), 170 mm (6.69") or 190 mm (7.48").

*For packing see page 37 ("Soft light packing")*



## DLH1000SPUS Tungsten Soft Light

The DLH1000SPUS is a 1000 W halogen soft light similar to the DLH1000S but fitted with a larger mounting yoke which allows the use of larger soft boxes. It features eight receptacles to accept the dedolight PanAura®/Octodome 5.

This light is ideal for drama productions or large sets requiring a broad soft source.

The DLH1000SPUS can be used as the tungsten companion to the DLH400SDT daylight version.

When a smaller size or packaging is required, please see DLH1000S.

Features the same adjustable speed ring as DLH1000S.

Diameter changeable in four steps:  
150 mm (5.9"), 170 mm (6.69"), 190 mm (7.48") or 210 mm (8.26").

*For packing see page 37 ("Soft light packing")*

### Technical Data: DLH1000S

Weight:	800 g (1.8 lbs)
Lamp:	See lamp table below
Cable length:	3 m (9.8')
Mounting:	16 mm (5/8") two axis receptacle and 28 mm (1 1/8") stud
Safety:	Protective glass tube
ON/OFF:	In-line switch
Socket:	G9.5

### Technical Data: DLH1000SPUS

Weight:	1200 g (2.6 lbs)
Lamp:	See lamp table below
Cable length:	3 m (9.8')
Mounting:	16 mm (5/8") two axis receptacle and 28 mm (1 1/8") stud
Safety:	Protective glass tube
ON/OFF:	In-line switch
Socket:	G9.5