

Productname: TRISTAR 6 Multi-Purpose Bi-color LED Light

SKU: ALP-TRISTAR-6

EAN: 8718591671869

Description

The TRISTAR 6, a super-bright Multi-Purpose Bi-color SMD LED light has a 3200K to 5600K color balance and is virtually unbreakable. The **Super-Bright SMD LED** technology provides an enormous bundle of light with great dimming control (100-10%).

You can use this very robust light on any camera and it offers an option to power it via a D-tap cable (included) to your V-mount or G- mount power supply. It can also easily substitute a 1x1 panel by using it on a light stand. Use two, or even three lights together for a perfect interview or studio set-up.

Together with the detachable metal barn door and diffusion filter you can create the perfect lighting conditions for any shoot.

Key features

- 240 long life Super-Bright SMD LEDs
- Robust housing for versatile camera purposes
- Smooth dimming control from Tungsten to Daylight
- Easily mounts on cameras, stands or handheld and has two mounting positions
- Powered by 4-Pin Mini XLR or Sony NP-F, Panasonic AG-VBR or Canon LP-E6 batteries (D-tap cable and brackets included)
- LCD display showing color temperature, brightness and battery capacity

Photometrics

	3200 K (Tungsten)		5600 K (Daylight)	
Distance	Footcandles	LUX	Footcandles	LUX
0.5 m / 1.64 ft.	180	1920	210	2120
1.0 m / 3.28 ft.	60	540	65	580
1.5 m / 4.92 ft.	35	310	40	330
2.0 m / 6.56 ft.	20	210	25	250



Specifications

Color temperature: 3200K – 5600K

Beam angle: 120°

Color rendering: > 90

LED life: approx. 30.000 hours

Power draw: approx. 15W

Power input:

Battery: Sony NP-F, Panasonic AG-VBR or Canon LP-E6

Mini XLR-4: 5V DC to 18V DC

Included in the package

- 1 TRISTAR 6 Multi-Purpose Bi-color SMD LED light
- 1 Detachable metal barn door system & diffusion filter
- 1 Robust ball head with 1/4" camera screw
- 1 D-Tap to 4-Pin Mini XLR power cable
- 1 Sony BP-U battery bracket
- 1 Canon LP-E6 battery bracket
- 1 Panasonic AG-VBR battery bracket
- 1 Owner's Manual

Measurements (L x W x H)

Dimension:	cm: 20.5 x 12 x 5 inch: 8.1 x 4.7 x 2.0
Weight:	kg: 0.4 lbs: 0.9

Shipping box dimensions (L x W x H)

Dimension:	cm: 24.5 x 15 x 10 inch: 9.6 x 5.9 x 3.9
Weight:	kg: 0.99 lbs: 2.18

