

Two legendary brands
ONE REVOLUTIONARY TRIPOD

flowtech-tripod.com 🕥







**75**mm **100**mm

Revolutionise the way you work with the world's fastest tripod.





# flowtech<sup>™</sup> Technology

Multi-award winning **flowtech™** is incredibly fast, lightweight and easy to set up and adjust compared to any other tripod, giving the camera operator ultimate versatility and improving their workflow.

Performance tested in extreme conditions, **flowtech™** is a revolution in tripod technology. Try it and join the revolution.



Two legendary brands **ONE REVOLUTIONARY TRIPOD** 



# An Evolution in Tripod Technology

flowtech<sup>™</sup>75 is for lighter camera set-ups to 20kg / 44lb flowtech<sup>™</sup>100 is for heavier camera set-ups to 30kg / 66lb.

> **Deploy and adjust your tripod in an instant:** Unique quick release brakes

**Easy to transport and exceptional torsional stiffness:** New ergonomic carbon fibre leg design

Capture extremely low and high shots: Versatile hinge lock mechanism

Fast stable setup in narrow spaces and on uneven terrain: Unique carbon fibre mid-level spreader\*

Superior performance and reliability: Extensive endurance and environmental testing

> \*Included as standard in all flowtech100 systems. Optional accessory for flowtech75.

# Unique Quick Release Brakes

Located at the top of the tripod, the quick release brakes enable the legs to be deployed simultaneously and can quickly adjust to the height that you need and the ground's surface - eliminating the need to bend over or manually adjust multiple brakes on each leg.

Deploy and adjust in an instant



## Ergonomic carbon fibre design

**flowtech™75** and **flowtech™100** are lightweight and easy to transport. The ergonomic design provides a comfortable shoulder position and strong magnetic leg locks ensure the tripod legs remain secured.



Lightweight and Exceptional Torsional Stiffness

Exceptional torsional stiffness ensures the tripod doesn't twist during panning movements.



# Versatile Hinge Lock

flowtech's unique hinge lock allows you to capture extremely low, ground-level shots along with higher shots. This effectively eliminates the need to take a set of baby legs to the shoot.







Capture extremely low and high shots

New easy to use foot mechanism

# New Foot Mechanism

flowtech's new quick attach and release foot mechanism easily adapts to the ground's surface.



Accessory Mount



flowtech's tripod bowl has 3 x 3/8in threads which can be used for attaching a magic arm or the flowtech attachment mount to hang a bag, battery pack or an optional carrying strap.

## Easily attach optional accessories



## Performance Tested

Tested in the most punishing environments, flowtech excels in sludge, sand and extreme temperatures. Furthermore, over 30,000 deployment cycles and 1.5 million clamp operations on an endurance rig, flowtech surpasses Sachtler and Vinten's stringent performance targets.





# Specifications

2-stage carbon fibre tripod with quick release brakes, mid-level spreader and rubber feet.

flowtech is compatible with all major 75mm and 100mm fluid heads and is ideally suited to fluid heads from the Sachtler or Vinten product families



SKU	Sachtler: 4585	Vinten: V4150-0003	Sachtler: 5585	Vinten: V4160-0003		
Payload	20kg / 44lb		30kg / 66lb			
Tripod bowl	75mm		100mm			
Tripod material	Carbon fibre		Carbon fibre			
Spreader material	Aluminum		Carbon fibre			
Weight (Tripod only)	2.9kg ;	/ 6.4lb	3.2kg - 7.01lb			
Weight (Tripod with rubber feet and mid-level spreader)	3.5kg	/ 7.7lb	i 4.1kg / 9.04lb			
Spreaderless mode height range	26 - 153cm /	10.2 - 60.2in	26 - 153cm / 10.2 - 60.2in			
Mid-level spreader height range	63 - 157cm /	24.8 - 61.8in	52 - 155cm / 20.5 - 61in			
Transport length	68cm /	′ 26.7in	68cm / 26.7in			
Extension	2	2x	1 2x			

flowtech<sup>™</sup>75

## flowtech<sup>®</sup>100

-----

# MANUFACTURING EXCELLENCE

## Internal expertise from design to despatch

**flowtech™** tripods are designed and engineered by Sachtler and Vinten at a purpose-built 66,000 square foot manufacturing facility in the United Kingdom. A team of 200 work together to create the industry's most popular camera support systems including the world's fastest tripod - **flowtech™**. The state-of-the-art, advanced carbon fibre cell produces tripod legs with remarkable strength, able to deliver exceptional torsional stiffness for the smoothest operation.



flowtech <sup>™</sup> 75						flowtech <sup>™</sup> 100 Available Systems			
Payload range		Å	Å	Å	Å				
Ace XL FT 75   1017MS	FSB 4 FT MS   0395	FSB 6 FT MS   0495	FSB 6 T FT MS   0465	FSB 8 FT MS   0795	FSB 8 T FT MS   0765	FSB 10 FT MS   S2045FTMS	FSB 10 T FT MS   S2046FTMS	DV 12 FT MS   1205FTMS	Video 15
2 - 8kg / 4.4 - 17.6lb	0 - 4kg / 0 - 8.8lb	1.5 - 8kg / 3.3 - 17.6lb	1.5 - 8kg / 3.3 - 17.6lb	1 - 10kg / 2.2 - 22lb	1 - 10kg / 2 - 22lb	4 - 12kg / 8.8 - 26.5lb	4 - 12kg / 8.8 - 26.5lb	1 - 15kg / 2 - 33lb	1 - 17
Ace XL fluid head (S2150- 0004) + tripod flowtech75 MS with mid-level spreader and rubber feet FT (4585)+ carry handle (S2051-1057) + padded bag (9116)	FSB 4 fluid head (0307) + tripod flowtech75 MS with mid-level spreader and rubber feet (4585) + carry handle (S2051-1057) + padded bag 75 (9116)	FSB 6 fluid head (0407) + tripod flowtech75 MS with mid-level spreader and rubber feet (4585) + carry handle (52051-1057) + padded bag 75 (9116)	FSB 6 T fluid head (0405) + tripod flowtech75 MS with mid-level spreader and rubber feet (4585) + carry handle (S2051-1057) + padded bag 75 (9116)	flowtech75 MS with mid-level	FSB 8 T fluid head (0705) + tripod flowtech75 MS with mid- level spreader and rubber feet (4585) + carry handle (52051- 1057) + padded bag 75 (9116)	FSB 10 fluid head (S2045-0001) + tripod flowtech100 MS with mid-level spreader and rubber feet (S585) + padded bag ENG (9104) + carry handle (S2051- 1057)	FSB 10 T fluid head (S2046- 0001) + tripod flowtech100 MS with mid-level spreader and rubber feet (5585) + padded bag ENG (9104)+ carry handle (S2051-1057)	DV 12 fluid head (1205) + tripod flowtech100 MS with mid-level spreader and rubber feet (5585) + padded bag ENG (9104) + carry handle (\$2051-1057)	Video 15 tripod flo mid-level feet (55 ENG (91 (1
Payload range		Å				Å		Á	
Vision blu	ie FT   VB-FT	Vision blue3 FT M	S   VB3-FTMS	Vision blue5 FT N	IS   VB5-FTMS	Vision 8AS FT M	S   V8AS-FTMS	Vision 10AS FT MS	5   V10AS-FTN
2.1 - 5kg	/ 4.6 - 11lb	3 - 6.6kg / 6	.6 - 14.6lb	5 - 12kg / 11	1 - 26.5lb	5.5 - 14.0kg /	12.1 - 30.9lb	6.5 - 17.0kg / 1	14.3 - 37.51
flowtech75 with case 75 (V4150-	nead (V4092-0001) + rubber feet and soft 1850) + carry handle 151-1057)	Vision blue3 fluid head ( tech75 MS (V4150-000 (V4150-1850) + carry h	3) and soft case 75	Vision blue5 fluid hea flowtech75 MS (V4150- 75 (V4150-1850) + ca 1057	0003) and soft case rry handle (S2051-	Vision 8AS (V4045- MS tripod (V4160-( (3358-3) + carry ha	0003) & soft case	Vision 10AS (V4046-00) tripod (V4160-0003) & s carry handle (S	soft case (3358









## o 15 FT MS | 1505FTMS

## Video 18 FT MS | 1811FTMS Cine 7+7 FT MS | 1910FTMS

## - 17kg / 2 - 37lb

eo 15 fluid head (1505) + od flowtech100 MS with t (5585) + padded bag

## 2 - 22kg / 4 - 48lb

## Video 18 fluid head (1811) + tripod Cine 7+7 fluid head (1910) + tripod flowtech100 MS with mid-level flowtech100 MS with mid-level level spreader and rubber spreader and rubber feet (5585) + spreader and rubber feet (5585) + Speedlevel Clamp (S2044-0001) Speedlevel Clamp (S2044-0001) G (9104) + carry handle + padded bag ENG (9104) + carry + padded bag ENG (9104) + carry (\$2051-1057) handle (\$2051-1057) handle (\$2051-1057)

2 - 22kg / 4 - 48lb

Vinten





## FTMS

## Vision 100 FT MS | VB100-FTMS

ech100 MS (3358-3) +

Vision 100 (3466-3), flowtech100 MS tripod (V4160-0003) & soft case (3340-3) + carry handle (S2051-1057)