aktiv



Level up with aktiv[™] the fluid head build for speed.

When you have just one change to capture the perfect shot, mount, level and lock the revolutionary aktiv[™] fluid head in seconds.

Sachtler's unique SpeedLevel[™] and SpeedSwap[™] technologies deliver the fastest way to place and position your camera; adjust the level in an instant without ever taking your eye off the action; get closer to the ground than ever before for extreme low-angle shorts or swap between a tripod, slider, or hand held without missing a beat. Capture the widest range of shots in the shortest time with aktiv.

- Level and lock your head in an instant without missing a second of action Unique SpeedLevel™ technology
- Visible from any height or angle day or night Innovative PrismBubble
- Capture extreme low angle shots right down to the ground Innovative streamlined mounting system
- Switch between tripod and slider in seconds Revolutionary SpeedSwap[™] system
- Create moving stories, whatever the weather. Performance tested to the extreme



Build for **Speed**.

Level up and lock your head in an instant.

Never miss the shot. aktiv™ fluid heads feature revolutionary Speed-Level™ technology. Release, level, and lock your head tightly into the perfect position without missing a second of action.

Visible from any height or angle - day or night.

Clear confirmation that the camera is level comes from the illuminated PrismBubble visible from any height or angle – day or night.

Capture extreme low-angle shots right. down to the ground.

Go lower than ever. aktivTM and flowtech[®] combine to provide a flexible one tripod solution delivering the widest height range. With no bowl clamp required, aktiv™ heads allow flowtech® tripods to go flat to the ground for the perfect low-angle shot.





Switch between tripod and slider in seconds.

aktiv6

Stay fast for ultimate creativity. aktiv™ fluid heads feature the unique SpeedSwap^{\rm TM} system, allowing lightning-fast camera swaps from a tripod to a slider without missing a beat. The perfect camera movement is just a SpeedSwap™ away.



0	
S	道

aktiv8

aktiv8T S2068T

aktiv10 \$20725

	S2064S	S2068S	S2068T	S2072S
Bowl	75 mm with SpeedSwap™	75 mm with SpeedSwap™	75 mm with SpeedSwap™	100 mm with SpeedSwap™
Payload range	0 - 8 kg / 0-17.6 lb	0 - 12 kg / 0 -26.5 lb	0 - 12 kg / 0 -26.5 lb	0 - 12 kg / 0 -26.5 lb
Counterbalance steps	15+0	15+0	15+0	15+0
Drag setting	3+0	7+0	7+0	7+0
Head Weight	2.6 kg / 5.7 lb	2.7 kg / 5.9 lb	2.8 kg / 6.2 lb	2.9 kg / 6.4 lb
Camera fitting	Sideload S	Sideload S	Touch & Go plate S	Sideload S

