


MARS 300 PRO

DUAL HDMI 300FT WIRELESS VIDEO TRANSMISSION SYSTEM



COMEBACK & REBORN



300FT
TRANSMISSION RANGE



0.08S
MINIMUM LATENCY



REAL-TIME
APP MONITORING



HDMI IN
& LOOPOUT



THUMBWHEEL
SWITCH MENU




SIDE OLED

PARAMETERS


	Transmitter	Receiver
Interface	HDMI Input (Type A Female) / HDMI Loop out (Type A Female) 2 Antenna Interfaces (RP-SMA Male) / USB Type-C	HDMI Output (Type A Female) / USB Type-C
Supply Interface	USB Type-C Supply: 5V/2A Battery Supply: 5-12V DC	USB Type-C Supply: 5V/2A Battery Supply: 5-12V DC
Power Consumption	<11W	<4W
Weight	136g ^②	128.5g
Deminsion	(L*W*H): 110*61*21mm ^③ The battery plate excluded	(L*W*H): 110*61*21mm The battery plate excluded
Input / Output Video Format	HDMI: 480p60 576p50 720p50/59.94/60 1080i50/59.94/60 1080p23.98/24/25/29.9/30 1080p50/59.94/60	HDMI: 480p60 576p50 720p50/60 1080i50/60 1080p24/25/30 1080p50/60
Frequency	5GHz	5GHz
Modulation Mode	OFDM	OFDM
Transmission Power	Maximum 21dBm	/
Receiver Sensitivity	/	-80dBm
Lowest Transmission Latency	0.08s	0.08s
Bandwidth	20MHz	20MHz

- MARS 300 PRO's enhanced transmitter has the external antennas.
- MARS 300 PRO's enhanced transmitter weighs 172.5g.
- MARS 300 PRO's enhanced transmitter dimension is L*W*H: 106*61*21.8mm(The battery plate excluded).

PACKING LIST



Transmitter



Receiver



User Guide



Expansion Accessory



Cold Shoe



USB Type-A to Type-C data cable

* Please subject to actual shipment as the standard if any difference in accessories.