



OG-3G-AM

OG-3G-AM has been discontinued.

Please click on openGear from the Products Menu and choose an updated Dashboard Compatible card for a current alternative.

The OG-3G-AM is a state of the art, openGear compatible, 8-channel AES audio Embedder/Disembedder with support for 3G-SDI input and output up to 1080p/60. Simple user controls allow channel enabling and mapping. A 10 BNC rear Open Gear connector module is included.

<https://www.aja.com/products/og-3g-am>

Video Formats

- 1x 3 Gb SDI (level A or B)
 - (2K) 2048 x 1080p 23.98, 24, 25, 29.97, 30, 50, 59.94, 60
 - (2K) 2048 x 1080PsF 23.98, 24, 25, 29.97, 30
 - (HD) 1920 x 1080p 23.98, 24, 25, 29.97, 30, 50, 59.94, 60
 - (HD) 1920 x 1080PsF 23.98, 24, 25, 29.97, 30
 - (HD) 1920 x 1080i 50, 59.94, 60
 - (HD) 1280 x 720p 50, 59.94, 60
- 1x 1.5 Gb SDI
 - (2K) 2048 x 1080p 23.98, 24, 25, 29.97, 30
 - (2K) 2048 x 1080PsF 23.98, 24, 25, 29.97, 30
 - (HD) 1920 x 1080p 23.98, 24, 25, 29.97, 30
 - (HD) 1920 x 1080PsF 23.98, 24, 25, 29.97, 30
 - (HD) 1920 x 1080i 50, 59.94, 60
 - (HD) 1280 x 720p 23.98, 24, 25, 29.97, 30, 50, 59.94, 60
- 1x 270 Mb SDI
 - (SD) 625i
 - (SD) 525i

Video Input Digital

- 1x 3G-SDI BNC, SMPTE-259/292/424

Video Output Digital

- 1x 3G-SDI BNC, SMPTE-259/292/424

Audio Input Digital

- 4x BNC

Audio Output Digital

- SDI embedded audio, 24-bit, 8-Channel
- 4x BNC

Audio Data Formats

- AES3 2003
- SMPTE ST 337

Digital Audio Converters

- 24-bit

Embedded Audio

- SDI embedded audio, 24-bit, 16-Channel*
 - SMPTE ST 272 (SD): 20-bit, 48 kHz synchronous
 - SMPTE ST 299 (3G/HD): 24-bit, 48 kHz synchronous
 - Incoming embedded audio can be passed, removed, or overridden
- *NOTE: 2048 x 1080p/PsF 29.97 and 30 formats support a maximum of 8-Channels embedded audio

Embed Path Audio Latency



(Time measured between audio input and video output connector):

- 1500 usec (SRC ON)
- 400 usec (SRC OFF)

Disembled Path Audio Latency

(Time measured between video input and audio output connector):

- 210 usec

User Interface

- AJA Mini-Config Software (via USB on front panel)

Slots

- Two slots required for each card

Size (w x d x h)

- openGear standard form factor, front slot and rear card
- Rear Card: OG-10-BNC-Rear
 - 10x BNC, SMPTE-259/292/424

Weight

- 0.5 lb (0.3 kg)

Power

- openGear frame compatible, 5.0 watts max per card

Environment

- Safe Operating Temperature: 0 to 40 C (32 to 104 F)
- Safe Storage Temperature (Power OFF): -40 to 60 C (-40 to 140 F)
- Operating Relative Humidity: 10-90% noncondensing
- Operating Altitude: <3,000 meters (<10,000 feet)