





DLH4x150S Tungsten Soft Light

A dedicated soft light for feature films or television series.

This soft light contains four 150W lamps with reflectors in one unit, providing light output just shy of a soft box mounted to the front of $\bar{\mathbf{a}}$ 2K Fresnel. Used with medium or large soft boxes, the light level at a given distance remains unchanged even though the size of the diffuser surface changes drastically. The illumination of the diffuser is perfectly even, whether one lamp or all lamps are in operation. Depending on the power option used, the four lamps can be dimmed individually allowing infinite variation of warm tone effects.

This light weight head does not require heavy mounting accessories.

Great versatility of powering options (see page 37). Requires DT4x150, DT24-3 or DT12-4 power supply.

DT4x150 **Power Supply**

The DLH4 \times 150S is powered from the DT4 \times 150 control unit which allows individual dimming of each lamp.


Any desired color temperature below 3400K can be chosen. Four different intensity levels can be set for each color temperature by activating one, two, three or four of the lamps. An infinite variation of intensity and warm tone effects can be achieved.

Technical Data: DLH4x150S

Weight: 800 g (1.8 lbs)

Four DL150-NB (24V / 150W) Lamp: DPOW4x150 - 2, 2 m (6') (Optional: DPOW4x150 - 8,8 m, 26') Cable length:

Mounting: To any $16 \, \text{mm} (5/8') \, \text{stud}$



Technical Data: DT4x150

Weight: 2.5 kg (5.5 lbs)

Input voltage: Available in four different versions:

240 V AC (DT4 x 150E+) 230 V AC (DT4 x 150E) 120 V AC (DT4 x 150U)

100 V AC (DT4 x 150J)

4×24V Output voltage:

Controls: Each output is individually dimmable

